



Product certificate K95847/04

Issued 2021-07-01

Replaces K95847/03

Page 1 of 2

Polyolefin sheeting without reinforcement for general applications

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Product Certification, Kiwa declares that legitimate confidence exists that the products supplied by

Plastika Kritis

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K546 "Polyolefin sheeting with or without reinforcement for general applications" dated October 5, 2020.

Ron Scheepers
Kiwa

Publication of the certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

288171015

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
Postbus 70
2280 AB RIJSWIJK
Tel. 088 998 44 00
Fax 088 998 44 20
info@kiwa.nl
www.kiwa.nl

Company

Plastika Kritis s.a.
R street, GR 71408 Iraklion, Crete
P.O. Box 1093
71110 IRAKLION
Greece
Tel. +30 2810308500
Fax +30 2810381328
info@plastikakritis.com
www.plastikakritis.com

Certification process
consists of initial and
regular assessment of:

- quality system
- product



Polyolefin sheeting without reinforcement for general applications

PRODUCT SPECIFICATION**General**

Polyolefin sheeting without reinforcement for general applications.

Further specification

The types and thicknesses, as indicated in undermentioned table, belong to this certificate.

Trade name and type name manufacturer	Type of foil	Effective foil thickness in mm (marked)			
		0.5	0.6	0.75	1.0
Kritiflex fPP	MB + UV	X	X	X	X

APPLICATION AND USE

The products are intended to be used for the following purposes:

- For storage of animal manure (foil type MB); as reservoirs, top covering or floating cover (type UV);
- Civil engineering, storage of water (not in contact with water for consumption), containment of water and water barrier; protection against the effects of spilling and incidental pollution (in general not for permanent contact with pollution)
- Top covers of landfill containment and storage of domestic and industrial garbage (applicable for foil type SO with a nominal thickness of at least 2,00 mm)
- In general for subsurface and covered applications.

In all cases consult paragraph 1.2 "Application and use" of BRL-K546 for possible applications per foil type and foil thickness.

MARKING

Obligated: The foil must be marked as follows:

- word mark Kiwa;
- type of membrane;
- trade name or registered trademark;
- material type;
- thickness of the membrane;
- charge number or production date (or code);
- Optional: the marking 'BRL K546'.

Marking by: relief mark on the membrane and on the packaging with indelible ink.

Positioning: on the membrane at least 1 x per 2 m and on the packaging per roll.

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- Plastika Kritis
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.